



# TOE JACKS



**13120**  
6 Ton Capacity



**13200**  
10 Ton Capacity



**13060**  
3 Ton Capacity

- Heat-treated medium-carbon steel cylinder
- Dual lift points
- Rotating pumping socket for multi-directional use
- Chrome plated ram guarantees longer seal life and optimum performance
- Hydraulic system is protected from internal damage by a patented by-pass mechanism, U.S. Patent No.5,946,912

| Model | Capacity | Minimum Toe Height | Maximum Toe Height | Minimum Head Height | Maximum Head Height | Hydraulic Lifting | Base Size Length | Base Size Width | G.W.    |
|-------|----------|--------------------|--------------------|---------------------|---------------------|-------------------|------------------|-----------------|---------|
| 13060 | 3 Ton    | 5/8"               | 5-3/4"             | 9"                  | 14-1/8"             | 5-1/8"            | 8-5/8"           | 7-1/2"          | 39 Lbs. |
| 13120 | 6 Ton    | 7/8"               | 6"                 | 10-1/2"             | 15-5/8"             |                   | 11"              | 7-1/2"          | 55 Lbs. |
| 13200 | 10 Ton   | 1-1/8"             | 6-1/4"             | 11"                 | 16-1/8"             |                   | 11-5/8"          | 9-1/4"          | 86 Lbs. |